

Display	Size Screen Type Aspect Ratio Display Area (HxV)mm Resolution (HxV) Pixel Pitch Back Light Unit Response Time Refreshing Frequency Display Color Brightness (typ) Brightness (min) Contrast Ratio (typ) High Haze Viewing Angle Life Time Display Orientation Operation Time	43" LCD 16:9 9730(H) × 5610(V) 3840(H) × 2160(V) 0.315 mm(H) × 0.315 mm(V) DLED 6.5ms 60Hz 107B(10bit) 450 cd/m2 400 cd/m2 4000 : 1 Yes,Haze 25% 178° 50,000 Hours Landscape & Portrait 7 days x 16 hours
Connectors	HDMI IN HDMI Output Coaxial/Optical Output Audio Output USB 2.0 USB 3.0 RS232 LAN(RJ45)(10M/100M/1000M) USB Type-C	2(HDMI 2.0) 1(HDMI Daisy chain,Up to 3*3) Optical*1 1,3.5mm 1 (F/W update / Media Play) 1 (F/W update / Media Play) 1 1 1(DP1.2,PD 65W,Network Sharing(100M))
System	System Version CPU GPU RAM ROM UI	Android 11 A55*4 MaliG51 MP2 4GB 32GB 4K
Audio	Speaker Type Power	Built-in Speaker 2x8W
Slot	OPS Slot WIFI Slot	No Yes, Included
Mechanisms	Bezel width(T/L/R/B) mm Structure Key Location & Number Handle Dimension (L*W*H) mm Thickness (W/ wall mount) (mm) Wall-hanging Screw VESA (Wall mounting Size) Dimension(package) L*W*H Net Weight(kg) Gross Weight(kg)	9,9/9,9/9,9/9,9 Metal Frame Metal Rear cover Back physical keys, 7 - 9730×561×63 mm 95(WIB4722A) M6*12 mm 200*200 mm 964×552×71 mm 9,35 13,3
Power	Power Requirements Standby Power Power Consumption(Typ) Power Consumption(Max)	100-240V~ 50/60Hz ≤0.5W 150W 250W
Accessories	Power Cord By Region Remote Control	3M*1 1 pcs
Environmental Conditions	Operation Temperature Operation Humidity Storage Temperature Storage Humidity Altitude Below	0°C - 40°C 10% - 90% -20°C -60°C 10% - 90% Below 5000 meters