

Display	Size	65"	
	Screen Type	LCD	
Connectors	Aspect Ratio	16:9	
	Display Area (HxV)mm	1428.48(H) × 803.52(V)	
	Resolution (HxV)	3840(H)×2160(V)	
	Pixel Pitch	0.372 mm(H) × 0.372 mm(V)	
	Back Light Unit	DLED	
	Response Time	8ms	
	Refreshing Frequency	60Hz	
	Display Color	1.07B(10bit)	
	Brightness (typ)	500 cd/m2	
	Brightness (min)	450 cd/m2	
	Contrast Ratio (typ)	1200:1	
	High Haze	Yes,Haze 25%	
	Viewing Angle	178°	
	Life Time	50000 Hours	
	Display Orientation	Landscape & Portrait	
	Operation Time	7 daysx16 hours	
	System	HDMI IN	3(HDMI 2.0)
		HDMI Output	1(HDMI Daisy chain,Up to 3*3)
		Coaxial/Optical Output	Optical*1
		Audio Output	1,3.5mm
USB 2.0		1 (F/W update / Media Play)	
USB 3.0		1 (F/W update / Media Play)	
RS232		1	
Audio	LAN(RJ45)(10M/100M/1000M)	2(IN/OUT)	
	USB Type-C	1(DP1.2,PD 65W,Network Sharing(100M))	
Slot	System Version	Android 11	
	CPU	A55*4	
	GPU	MaliG51 MP2	
	RAM	4GB	
	ROM	32GB	
Mechanisms	UI	4K	
	Speaker Type	Built-in Speaker	
Power	Power	2x10W	
	OPS Slot	Yes, 80 Pin OPS	
Accessories	WIFI Slot	Yes, included	
	Environmental Conditions	Bezel width(T/L/R/B) mm	15.9/15.9/15.9/15.9
		Structure	Metal Frame Metal Rear cover
		Key Location & Number	Back physical keys, 7
		Handle	2
		Dimension (L*W*H) mm	1463.3x838.3x81.6
		Thickness (W/ wall mount) (mm)	101.4(WIB9080A)
		Wall-hanging Screw	M8*25mm
		VESA (Wall mounting Size)	600x400mm
		Dimension(package) L*W*H	1620*208*942mm
		Net Weight(kg)	25.4
		Gross Weight(kg)	33.3
		Power Requirements	100-240V~ 50/60Hz
		Standby Power	≤0.5W
		Power Consumption(Typ)	165W
Power Consumption(Max)	335W		
Accessories	Power Cord By Region	3M*1	
	Remote Control	1 pcs	
Environmental Conditions	Operation Temperature	0°C - 40°C	
	Operation Humidity	10% - 90%	
	Storage Temperature	-20°C - 60°C	
	Storage Humidity	10% - 90%	
	Altitude Below	Below 5000 meters	

